


11 Disassembly and Reassembly



This section of the service manual describes the disassembly and reassembly procedures for the LDP21WS TFT-LCD monitors.



⚠ WARNING: This monitor contains electrostatically sensitive devices. Use caution when handling these components.

11-1 Disassembly

- ⚠ Cautions:**
1. Disassembly stand on the flat desk.
 2. Disconnect the monitor from the power source before disassembly.

Description	Picture Description
1. To take out the two screws for the stand disconnect.	
	

Description	Picture Description
<p>2. Take out 3 screws on rear cabinet. Use the Jig and Separate Cover Rear.</p>	
<p>3 - Separate Function cable from Main Board. - Separate Lamp wire shield - Separate AV cover</p> <p>4. Separate lamp wire</p>	

Description	Picture Description
<p>5. - Separate LVDS cable form the Panel. - Separate the 5 screws from the PBA Board.</p>	 A close-up photograph showing a hand using a small tool to separate the LVDS cable from the panel. The cable is connected to a metal bracket with two screws. The text 'LTM2100' is visible on the metal part.
	 A photograph of the PBA Board (Printed Board Assembly) showing the location of the five screws that need to be removed. The screws are circled in red. The board is green and has various components and labels, including 'E-PAS' and '1533 PM'.

11-2 Reassembly

Reassembly procedures are in the reverse order of disassembly procedures.

Memo