



13 Circuit Descriptions

13-1 Block description



Bordeaux consists of three main blocks


1. Main board : Video signal processing
2. IP board : Power supply & Inverter
3. T-con board : LCD Panel control



Bordeaux consists of three main blocks


1. Main board : Video signal processing
2. SMPS : Power supply
3. T-con board : LCD Panel control

13-2 Main Block




13-3 SMPS Board

13-3-1 26", 32" Power Block




13-3-2 26", 32" SMPS Diagram




Output Name	Output Voltage			Output Current			Load Characteristics	PCB Loc.	Usage	Remark
	Normal	Regulation(%)	Variable Range	Min	Typical	Peak				
24V	24.5V	± 4	23.52V ~25.48V	0.1V	3.0V	4.0V	Pulsating	Main B'D	Drive	-
5.3V	5.3V	± 5	5.13V ~5.67V	0.1V	3.0V	5.0V	Constant	Main B'D	Drive, Logic, Buffer, Image Digital	-
13V	12.7V	± 7	11.9V ~13.7V	0.01V	0.3V	0.5V	Constant	Main B'D	Image Analog	-
Vamp	9.2V	± 4	8.83V ~9.57V	0.01V	0.3V	1.1V	Constant	Main B'D	Sound	-
ST-BY	8.0V	± 5	5.58V ~8.5V	0.1V	0.3V	0.6V	Constant	Main B'D	Stand-by	-

13 Circuit Descriptions


13-3-5 37" Power Block




13-3-6 37" SMPS Diagram



13-3-7 40, 46" IP Board



13-3-8 40, 46" IP Board



Memo