现货库存、技术资料、百科信息、热点资讯，精彩尽在鼎好！


ALPHA & OMEGA SEMICONDUCTOR, LTD

AO4607
Complementary Enhancement Mode Field Effect Transistor


General Description
The AO4607 uses advanced trench technology MOSFETs to provide excellen $R_{DS(ON)}$ and low gate charge. The complementary MOSFETs may be used in inverter and other applications. A Schottky diode is co-packaged with the n-channel FET to minimize body diode losses. *AO4607 is Pb-free (meets ROHS & Sony 259 specifications). AO4607L is a Green Product ordering option. AO4607 and AO4607L are electrically identical.*

Features
n-channel	p-channel
V_{DS} (V) = 30V	-30V
I_D = 6.9A (V_{GS}=10V)	-6A (V_{GS}=1-0V)
$R_{DS(ON)}$	$R_{DS(ON)}$
< 28mΩ (V_{GS}=10V)	< 35mΩ (V_{GS} = -10V)
< 42mΩ (V_{GS}=4.5V)	< 58mΩ (V_{GS} =- 4.5V)


SCHOTTKY
VDS (V) = 30V, IF = 3A, VF<0.5V@1A



SOIC-8



n-channel



p-channel

Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	Max n-channel	Max p-channel	Units
Drain-Source Voltage		V_{DS}	30	-30	V
Gate-Source Voltage		V_{GS}	±20	±20	V
Continuous Drain Current [A]	T_A=25°C	I_D	6.9	-6	A
	T_A=70°C		5.8	-5	
Pulsed Drain Current [B]		I_{DM}	30	-30	
Power Dissipation	T_A=25°C	P_D	2	2	W
	T_A=70°C		1.28	1.28	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	-55 to 150	°C

Parameter		Symbol	Maximum Schottky	Units
Reverse Voltage		V_{DS}	30	V
Continuous Forward Current [A]	T_A=25°C	I_D	3	A
	T_A=70°C		2	
Pulsed Diode Forward Current [B]		I_{DM}	20	
Power Dissipation [A]	T_A=25°C	P_D	2	W
	T_A=70°C		1.28	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	°C

Thermal Characteristics: n-channel, Schottky and p-channel						
Parameter		**Symbol**	**Device**	**Typ**	**Max**	**Units**
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	n-ch	48	62.5	°C/W
Maximum Junction-to-Ambient [A]	Steady-State		n-ch	74	110	°C/W
Maximum Junction-to-Lead [C]	Steady-State	$R_{\theta JL}$	n-ch	35	60	°C/W
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	p-ch	48	62.5	°C/W
Maximum Junction-to-Ambient [A]	Steady-State		p-ch	74	110	°C/W
Maximum Junction-to-Lead [C]	Steady-State	$R_{\theta JL}$	p-ch	35	40	°C/W
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	Schottky	47.5	62.5	°C/W
Maximum Junction-to-Ambient [A]	Steady-State		Schottky	71	110	°C/W
Maximum Junction-to-Lead [C]	Steady-State	$R_{\theta JL}$	Schottky	32	40	°C/W

N-Channel + Schottky Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=250µA, V_{GS}=0V	30			V
I_{DSS}	Zero Gate Voltage Drain Current. (Set by Schottky leakage)	V_R=30V		0.007	0.05	mA
		V_R=30V, T_J=125°C		3.2	10	
		V_R=30V, T_J=150°C		12	20	
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}=±20V			100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS} I_D=250µA	1	1.9	3	V
$I_{D(ON)}$	On state drain current	V_{GS}=4.5V, V_{DS}=5V	20			A
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=10V, I_D=6.9A		22.5	28	mΩ
		T_J=125°C		31.3	38	
		V_{GS}=4.5V, I_D=5.0A		34.5	42	mΩ
g_{FS}	Forward Transconductance	V_{DS}=5V, I_D=6.9A	10	15.4		S
V_{SD}	Body-Diode+Schottky Forward Voltage	I_S=1A		0.45	0.5	V
I_S	Maximum Body-Diode+Schottky Continuous Current				5.5	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=15V, f=1MHz		680	820	pF
C_{oss}	Output Capacitance (FET+Schottky)			131		pF
C_{rss}	Reverse Transfer Capacitance			77		pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz		3	3.6	Ω
SWITCHING PARAMETERS						
Q_g(10V)	Total Gate Charge	V_{GS}=10V, V_{DS}=15V, I_D=6.9A		13.84	16.6	nC
Q_g(4.5V)	Total Gate Charge			6.74		nC
Q_{gs}	Gate Source Charge			1.82		nC
Q_{gd}	Gate Drain Charge			3.2		nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=10V, V_{DS}=15V, R_L=2.2Ω, R_{GEN}=3Ω		4.6		ns
t_r	Turn-On Rise Time			4.1		ns
$t_{D(off)}$	Turn-Off DelayTime			20.6		ns
t_f	Turn-Off Fall Time			5.2		ns
t_{rr}	Body-Diode+Schottky Reverse Recovery Time	I_F=6.9A, dI/dt=100A/µs		13.7	16.5	ns
Q_{rr}	Body-Diode+Schottky Reverse Recovery Charge	I_F=6.9A, dI/dt=100A/µs		4.1		nC

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1in ^{2} FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The value in any given application depends on the user's specific board design. The current rating is based on the t ≤ 10s thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C. The $R_{\theta JA}$ is the sum of the thermal impedence from junction to lead $R_{\theta JL}$ and lead to ambient.

D. The static characteristics in Figures 1 to 6 are obtained using 80 µs pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in ^{2} FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The SOA curve provides a single pulse rating.

F. The Schottky appears in parallel with the MOSFET body diode, even though it is a separate chip. Therefore, we provide the net forward drop, capacitance and recovery characteristics of the MOSFET and Schottky. However, the thermal resistance is specified for each chip separately

Rev 4: Sept 2005

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: N-CHANNEL




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body diode with parallel Schottky characteristics (Note F)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: N-CHANNEL




Figure 7: Gate-Charge characteristics




Figure 8: Capacitance Characteristics: MOSFET + Parallel Schottky




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance

P-Channel Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=-250µA, V_{GS}=0V	-30			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=-24V, V_{GS}=0V			-1	µA
		T_J=55°C			-5	
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}=±20V			±100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS} I_D=-250µA	-1.2	-2	-2.4	V
$I_{D(ON)}$	On state drain current	V_{GS}=-10V, V_{DS}=-5V	30			A
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=-10V, I_D=-6A		28	35	mΩ
		T_J=125°C		37	45	
		V_{GS}=-4.5V, I_D=-5A		44	58	mΩ
g_{FS}	Forward Transconductance	V_{DS}=-5V, I_D=-6A		13		S
V_{SD}	Diode Forward Voltage	I_S=-1A,V_{GS}=0V		-0.76	-1	V
I_S	Maximum Body-Diode Continuous Current				-4.2	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=-15V, f=1MHz		920	1100	pF
C_{oss}	Output Capacitance			190		pF
C_{rss}	Reverse Transfer Capacitance			122		pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz		3.6	4.4	Ω
SWITCHING PARAMETERS						
Q_g(10V)	Total Gate Charge (10V)	V_{GS}=-10V, V_{DS}=-15V, I_D=-6A		18.5	22.2	nC
Q_g(4.5V)	Total Gate Charge (4.5V)			9.6		nC
Q_{gs}	Gate Source Charge			2.7		nC
Q_{gd}	Gate Drain Charge			4.5		nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=-10V, V_{DS}=-15V, R_L=2.7Ω, R_{GEN}=3Ω		7.7		ns
t_r	Turn-On Rise Time			5.7		ns
$t_{D(off)}$	Turn-Off DelayTime			20.2		ns
t_f	Turn-Off Fall Time			9.5		ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=-6A, dI/dt=100A/µs		20	24	ns
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=-6A, dI/dt=100A/µs		8.8		nC

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1in ^{2} FR-4 board with 2oz. Copper, in a still air environment with T_A =25°C. The value in any given application depends on the user's specific board design. The current rating is based on the t ≤ 10s thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C. The $R_{\theta JA}$ is the sum of the thermal impedence from junction to lead $R_{\theta JL}$ and lead to ambient.

D. The static characteristics in Figures 1 to 6,12,14 are obtained using 80 µs pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in ^{2} FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The SOA curve provides a single pulse rating.

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE. Rev 4: Sept 2005

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: P-CHANNEL




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: P-CHANNEL




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance