

Monitor

◀ Previous ▲ Top ▶ Next

76i



Feature

- Multi-synchronous compatibility from 640 x 480 up to 1024 x 768 @ 60 Hz NI, and flicker-free at 800 x 600 @ 75 Hz NI.
- VESA DDC2B and DDC1 compliant for true plug and play performance, when used with plug and play compatible video cards and PCs.
- The flat-square tube, Invar shadow mask, and non-glare screen coating all combine for vivid images and high contrast for reduced eye strain.
- Meets MPR II low-emission standards and surpasses EPA Energy Star and VESA DPMS energy consumption requirements for safer, more economical operation.
- Digital microprocessor controls includes 12 user settable and 5 factory preset adjustments.
- Detachable tilt/swivel base allows for optimal placement and positioning in any environment.
- Autosensing 90-264 VAC power requirements for worldwide compatibility. Free of any CFCs. Manufactured in ISO 9001 certified factory.

CRT Size/Type	17" FST (16" VIS), Invar mask, dark body tube, dark glass faceplate
Display Size	11.8" x 8.9" normal, 14.8" x 9.6" full screen
Display Colors	Unlimited colors
CRT Transmission	52.5%
CRT Pitch	.39mm Dot
CRT Coating	Non-glare silica
Phosphor	P22, medium short persistence
Maximum Flicker-Free Resolutions	640 x 480/75 Hz NI

	800 x 600/75 Hz NI
Maximum Resolution	1024 x 768/60 Hz NI, 87 Hz(I)
Display Capability	Auto-sync within scan frequencies
Horizontal Scanning Frequencies	30-50 KHz
Vertical Scanning Frequencies	50-90 Hz
Input Signal	RGB Analog
Video Bandwidth	65 MHz
Input Signal Connectors	15 pin D-sub
Cable Supplied	15 pin D-sub connector, 48" detachable
Monitor Control Type	Digital microprocessor control with LED
Memory Modes	5 factory presets, 12 user settable
VESA Plug and Play Level	DDC2B, DDC1
Front Panel Buttons/Controls	Power, brightness, contrast, select(+/-) adjust(+/-)
Digital Adjustment	Horizontal/vertical size and position, side pincushion, trapezoid
Power Requirements	90-264 VAC, 47-63 Hz
DPMS Power Consumption	
On:	100 Watts
Stand-by:	15 Watts
DPMS Off:	8 Watts
Detachable Tilt/Swivel Base	Tilt 5-13.5, swivel 45/45
Dimensions (WxHxD) w Base	16.3" x 16.5" x 17.5"
Weight Net	38.5 lbs.
Packed in Carton	46.2 lbs.
40 ft. Container Quantity	368 sets, individual
Mean Time Between Failure	50,000 hours
Safety/Regulatory	UL, FCC-B, CSA, DHHS, TUV-GS, SEMKO, NEMKO, ROV, ISO 9421-3, FTZ-B, CE-MARKS, MPR II, EPA ENERGY STAR
Warranty	3 years limited on parts, labor, CRT
UPC #	719192 163355

Please download Acrobat Reader to print PDF file



Printable PDF Format